



New Horizon Shutters International, LLC
7259A Spa Road
North Charleston, SC 29418
www.NewHorizonShutters.com

TOUCH-UP PAINT INSTRUCTIONS

New Horizon Shutters uses a high-performance two (2) part catalyzed fast-drying industrial coating. This paint is designed for spray applications only, so an air brush or aerosol style sprayer is recommended. A brush can be used with a dabbing technique on small areas (i.e. a nick or puncture). HOWEVER, because of the extremely fast dry times, brushing generally yields poor results.

MIXING INSTRUCTIONS

Mix paint thoroughly. Following the mixing ratios below, pour paint into a small graduated mixing cup then mix in catalyst. Add reducer as needed (again following ratios below).

MIXING RATIO

3 parts paint to 1 part hardener (3:1).
If mixture needs to be thinned, up to 0.6 parts Acetone may be added (3:1:0.6).

TIPS

Excessive thinning (beyond the 3:1:0.6 ratio) will compromise coating durability and coverage.

Once catalyzed, paint pot life is ONLY 30 MINUTES!!! After 30 minutes, the paint may still flow and spray, however it will be too far along in the catalyzing process to yield acceptable results.

Denatured alcohol works well for clean-up.

Apply paint with a Preval® Sprayer (or similar) using a feathering technique. Preval® Sprayers can be found at local paint supplier, hardware store, or automotive store.